

	Modelo	Capacidad frigorífica <sup>1</sup>	Tensión nominal <sup>2</sup>	Dimensiones (HxAxP)	Normas / homologaciones		
					UL	cUL	CE
	EB 32 WT	3200 W	400 V 3 ~	1225 x 600 x 760 mm	x <sup>1</sup>	x <sup>1</sup>	x
	EB 44 WT	4400 W			x <sup>1</sup>	x <sup>1</sup>	x
	EB 65 WT	6500 W	400 V 3 ~ / 460 V 3 ~	1225 x 600 x 760 mm	x <sup>1</sup>	x <sup>1</sup>	x
	EB 80 WT	8000 W			x <sup>1</sup>	x <sup>1</sup>	x
	EB 95 WT	9500 W	400 V 3 ~ / 460 V 3 ~	1400 x 855 x 800 mm	x <sup>1</sup>	x <sup>1</sup>	x
	EB 140 WT	14000 W			x <sup>1</sup>	x <sup>1</sup>	x
	EB 160 WT	16000 W			x <sup>1</sup>	x <sup>1</sup>	x

<sup>1</sup> performance data based on 50 Hz operation

<sup>2</sup> different voltages available on request

x available

x<sup>1</sup> available, ETL certification based on UL508A

©2018, Pfannenberg Europe GmbH